



## 21.5" Fanless Industrial Panel PC – IPC215-60/I3/I5/I7



- Industrial 21.5" IPC LCD with 60 K lifetime LED Backlight.
- Windows system or android system for option.
- Support Wide Operating Temperature 0~50°C.
- Flat panel with projected capacitive touchscreen.
- Front panel compliant with IP65.
- Powered by Celeron J1900, intel Core 3rd-4th-8th-i3/i5 Processor, intel core i7 processor.

<b>System</b>		Model IPC215-60/I3/I5/I7
Processor	Intel Celeron/ Core i3/i5/i7 Processor	
System Memory	4GB RAM, 1XDD3, upto 32 GB	
<b>External I/O</b>		
USB	1 x USB 3.0, 1x USB 2.0	
Serial	2 x RS232 COM0, COM1	
Audio	1X 3.5mm audio	
LAN	2 x Gigabit LAN, RTL8111F, 10Mbps/100Mbps/1000Mbps	
Video Out	External HDMI and VGA outputs available	
Power	Power Connector 230 AC	
<b>Internal I/O</b>		
Serial/Parallel	4 x RS232 header, 1 x LPT header	
USB	4 x USB 3.0	
Onboard Expansion	1 x Mini-PCIe	
<b>Storage</b>		
HDD	Upto 512 GB SSD	
<b>Display</b>		
Display Type	21.5" aSi TFT LCD	
Resolution	1920 x 1080 pixels	
Max Color	16.7 M	
Luminance	300 cd/m <sup>2</sup>	
Viewing Angle	178°/178°	
Contrast Ratio	1000:1	
Backlight Lifetime	60,000 hrs	
TouchScreen Type	Capacitive 10 Point Multi Touch	
<b>Mechanical</b>		
Construction	Front bezel: tempered glass, casting aluminum.	
IP Rating	IP65 Front Side (except I/O side)	
Mounting	Panel Mount, Vesa mount	
Dimension	508 X 305 X 68 mm	



**Environment**

Operating Temperature 0°C ~ +50°C  
 Storage Temperature -20°C ~ +60°C

**Mounting Drawing**

